



STRING INVERTER HYX-S75K/100K/ 110K/120K-T



Safe & Reliable

- Type II DC/AC surge protection, lightning-proof
- 300m AFCI detection with 0.5s rapid shutdown
- IP66, 1400+ cumulative rigorous tests
- PV optimizers compatible, module-level shutdown

Convenient & User-Friendly

- Compact and lightweight design, plug-and-play installation
- App-based quick setup
- Intelligent layout with rapid module-level visualization

Profitable & Efficient

- 40A design, dynamic MPPT efficiency of 99.9%
- Built-in PID repair, improving overall system performance
- AI dynamic MPPT, boosting power generation by 5%

Smart & Manageable

- Module-level monitoring for precise fault positioning
- Intelligent IV diagnostics for precise fault identification
- Real-time monitoring with OTA for online maintenance

Product Model	HYX-S75K-T	HYX-S100K-T	HYX-S110K-T	HYX-S120K-T
PV Input				
Max. Input Voltage		1,100V		
Nominal Input Voltage		620V		
Start-up Voltage		160V		
MPPT Operating Voltage Range		140 - 1,000V		
MPPT Full Load Voltage Range		500 - 850V		
Max. Input Current Per MPPT		40A		
Max. Input Current Per String		20A		
Max. Short-Circuit Current		50A		
Number of MPPT		10		
Max. Input Number Per MPPT		20		
AC Output				
Nominal Output Power	75kW	100kW	110kW	120kW
Max. Apparent Power	82.5kVA	110kVA	121kVA	132kVA
Nominal Output Voltage		3L / N / PE, 220 / 380V, 230 / 400V		
Nominal AC Grid Frequency		50 / 60Hz		
Nominal Output Current	113.9A	151.9A	167.1A	182.3A
Max. Output Current	125.3A	167.2A	185.7A	190.5A
Adjustable Power Factor		0.8 leading...0.8 lagging		
THDi		< 3%		
Efficiency				
Max. Efficiency		98.8%		
European Weighted Efficiency		98.3%		
MPPT Efficiency		99.9%		
Protection				
Active Anti-islanding Protection		General Electric Frequency Shift		
Residual Current Monitoring		Yes		
DC Reverse Polarity Protection		Yes		
DC Switch		Yes		
AC Short-circuit Protection		Yes		
AC Overvoltage Protection		Yes		
AC Overcurrent Protection		Yes		
DC Surge Protection		Type II		
AC Surge Protection		Type II		
Ground Fault Detection		Yes		
AFCI		Optional		
PID recovery		Optional		
General Data				
Operating Temperature Range		-30 to + 60°C		
Relative Operating Humidity		0 - 100 %RH		
Operating Altitude		4,000m		
Cooling		Smart Air Cooling		
Display		LED/ WLAN+App		
Communication		RS485 / 4G / WIFI / HPLC		
Weight		94kg		
Dimensions (W*H*D)		1000*730*375mm		
Topology		Non-Isolated		
Degree of Protection		IP66		
Overvoltage Level		PV II / AC III		

GoRewatt Energy Hub Pvt Ltd

Sy.No, 78/3, Ramakrishnapura Rd, Iggalur, Chandapura,
 Bengaluru, Karnataka - 560081

Call Us: +91 767676 5959 E-Mail: sales@gorewatt.com
 www.gorewatt.com

